



1D & 2D



CMOS



RS232



USB



1.2M
drop



IP42



**HR2081 Panga
III**
Handheld Scanners

Features

Outstanding Performance.

The HR2081 Panga III is equipped with an exceptional CPU that efficiently captures high-density, high-volume, and distorted barcodes printed on paper or displayed on screens.

Cost-effective Solution

The HR2081 Panga III offers an attractive price, providing a cost-effective data capture solution. This allows businesses to enjoy the capabilities of a 2D barcode scanner at the price of a 1D.

Elegant Appearance

The HR2081 Panga III features an aesthetic and ergonomic design, ensuring user comfort and productivity during intensive handheld scanning. Moreover, its appearance allows it to blend seamlessly into any environment, whether in healthcare or retail.

Durable Construction

The HR2081 Panga III is designed to withstand tough environments. With an IP42 rating and resistance to drops of up to 1.2 meters, it can handle the challenges of daily tasks.

Suggested industries



Retail



Hospitality



Healthcare



HR2081 Panga III Technical specifications

Data Capture

1D	Code 11, Code 128, Code 39, GS1 128 (UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code 93, UPC A, UPC E, Coupon, GS1 Composite, EAN 8, EAN 13, ISBN/ISSN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 25, ITF6, ITF 14, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS)
2D	PDF417, Micro PDF417, M i cro QR, QR Code, Data Matrix, Aztec.
Image Sensor	640×480 CMOS
Aiming	Red LED (625nm)
Illumination	White LED
Resolution	≥3mil
Depth of Field EAN 13 (13mil)	50mm - 260mm
Depth of Field Code 39 (5mil)	50mm - 115mm
Depth of Field PDF417 (6.7mil)	50mm - 120mm
Depth of Field DataMatrix (10mil)	35mm - 125mm
Depth of Field QR (15mil)	30mm - 170mm
Field of View Horizontal	45°
Field of View Vertical	34°
Scan Angle Roll	360°
Scan Angle Pitch	±55°
Scan Angle Skew	±55°
Minimal Print Contrast	20%

Physical

Current @ 5VDC Operating	190mA (typical), 201mA (max.)
Current @ 5VDC Standby	35mA
Dimensions (mm)	145×101×68 mm (LxWxH)
Input Voltage	5VDC±5%
Interfaces	RS 232, USB
Notifications	Beep, LED
Power Consumption	950mW (typical)
Weight	111g

Environmental

Operating Temperature	20°C to 60°C (4°F to 140°F)
Storage Temperature	40°C to 70°C (40°F to 158°F)
Humidity	5%~95% (non condensing)
Electro Static Discharge (ESD)	±15 KV (air discharge); ±8 KV (direct discharge)
Drop	1.2m
IP Rating	IP42

Newland AIDC EMEA

Email address: info@newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2025, all rights reserved

HR2081 Panga III Technical specifications

Accessories

Standard	USB cable
Optional	Foldable stand NLS-STD20-20

Certifications

Hardware	FCC Part15 Class B, CE EMC Class B, RoHS
----------	--

Warranty

Standard	5 Years
----------	---------